

(12) **United States Patent**
Büstgens

(10) **Patent No.:** **US 9,638,350 B2**
(45) **Date of Patent:** **May 2, 2017**

(54) **MICRO PILOT VALVE**

(71) Applicant: **Burkhard Büstgens**, Gundelfingen
(DE)

(72) Inventor: **Burkhard Büstgens**, Gundelfingen
(DE)

(73) Assignee: **Burkhard Büstgens**, Gundelfingen
(DE)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 34 days.

(21) Appl. No.: **14/390,059**

(22) PCT Filed: **Mar. 28, 2013**

(86) PCT No.: **PCT/DE2013/000166**

§ 371 (c)(1),

(2) Date: **Oct. 2, 2014**

(87) PCT Pub. No.: **WO2013/149610**

PCT Pub. Date: **Oct. 10, 2013**

(65) **Prior Publication Data**

US 2015/0316172 A1 Nov. 5, 2015

(30) **Foreign Application Priority Data**

Apr. 3, 2012 (DE) 10 2012 006 658

(51) **Int. Cl.**

F16K 11/044 (2006.01)

F16K 99/00 (2006.01)

(Continued)

(52) **U.S. Cl.**

CPC **F16K 99/0048** (2013.01); **B41J 2/04**
(2013.01); **B41J 2/14282** (2013.01);

(Continued)

(58) **Field of Classification Search**

CPC Y10T 137/7761; Y10T 137/86501; Y10T
137/8667–137/8671; Y10T 137/86815;
(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,152,612 A * 10/1964 Avery F16K 31/006
137/625.4

3,236,452 A * 2/1966 Bordeaux F01N 3/2053
137/110

(Continued)

FOREIGN PATENT DOCUMENTS

DE 19946833 A1 5/2001
DE 102007028673 B3 8/2003

OTHER PUBLICATIONS

International Search Report of PCT/DE2013/000166.

Primary Examiner — William McCalister

(57) **ABSTRACT**

The invention relates to a micro pilot valve 1, which is characterized by a micro cavity 2, which is connected with valve outlet 3, a first micro opening 4 between micro cavity 2 and a first pressure level 5, a second micro opening 6 between micro cavity 2 and a second pressure level 7, a sealing element 8 within micro cavity 2, which is movable between the micro openings, and which in a first end position closes micro opening 4 and in a second end position micro opening 6, whereas the control pressure in the first end position adopts the value of the second pressure level 7 and in the second end position the value of the first pressure level 5, and a micro actuator 10, which actuates sealing element 8 via a transfer element, which protrudes at least through one of the micro openings.

8 Claims, 3 Drawing Sheets

